

IN1188HD

Ultra-Portable LED Projector

Part #: IN1188HD

InFocus

The IN1188HD ultra-portable projector is built to perform, with HDMI input, high brightness, ultra-long-lasting images, and unbeatable quality and color. Featuring a compact, light weight design, the IN1188HD is perfect for business travelers, or anyone who needs to take their presentation on the road.

Key Features

- ◆ Quantum Color Engine for vivid, ultra-long-lasting images
- ◆ Amazing 30,000-hour light source
- ◆ Green, mercury-free technology
- ◆ 3000 lumens and full HD resolution
- ◆ Support for AirPlay and MiraCast



Quantum Color Engine

The IN1188HD is powered by the InFocus [Quantum Color Engine](#) for exceptional image quality over years of continuous operation. The Quantum Color Engine is based on solid-state illumination technology, and is tested for over 200 unique color parameters to ensure the most vivid images possible. A massive color gamut, up to 40% bigger than leading competitors, and high color luminosity ratio bring your screen to life. With no color decay, you can enjoy remarkable images for over 3 years of 24/7 operation or over 10 years of business hour operation.

Superior Images

Get quality images and true-to-life colors with DLP technology with InFocus BrilliantColor implementation. 3,000 lumens mean bright, clear images even with the lights on, and 1,000,000:1 contrast ratio adds sharpness with darker blacks and whiter whites.

Greener Technology, Greater ROI

Solid-state technology means your projector will last an amazing 30,000 hours, with an environmentally friendly mercury-free design. No lamps to replace means less hassle and fewer added expenses over time

Specifications*

Projector	IN1188HD
Resolution – Native	Full HD (1920 x 1080)
Display Technology	DLP with LED light source
Video Standard Compatibility	NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Projector		IN1188HD
Speakers		Mono 3W x 1
Lamp Brightness		3,000 lumens
Lamp Life		30,000 hours
Lamp Power		106W
Contrast Ratio		1,000,000:1
Number of Colors		1.08 billion
Synch Scan Frequency – Horizontal		15 ~ 103 KHz
Synch Scan Frequency – Vertical		24 ~ 120 KHz
Aspect Ratio		16:9
Aspect Ratio Compatibility		4:3, 16:10, 2.35:1, 1:1, 2:1, 13:9, 15:9, 5:4
Projection Lens F-Stop – Minimum		1.70
Image Size – Minimum		30 in
Image Size – Maximum		300 in
Projection Offset		103%
Keystone Correction		± 40°
Connectors – Inputs		3.5mm audio, Composite video, USB A x2, HDMI, VGA
Connectors – Outputs		3.5mm audio output
Audible Noise		< 33 dBA at 0°F / -17.8°C
Audible Noise – Eco Mode		< 26 dBA at 0°F / -17.8°C
Included Accessories		Power cord, Remote (no batteries), HDMI Cable, Documentation, Quick Start Guide, Carrying case, User Manual (CD), Lens cap
3D Support		1080p @ 60Hz, All HDMI 1.4a 3D formats, DLP Link 3D glasses required
Video Player Compatibility		AVI, MKV, MP4, MPEG-1 (MPG, MPEG), WMV, MOV
Photo Viewer Compatibility		JPEG and JPG, Bitmap (BMP)
Music Player Compatibility		MP3, WMA, AAC, WAV
Power Consumption		215.0W max
Power Consumption – Standby Mode		0.5W max
Power Standard		AC 100 to 240V, 50/60
Documentation Languages		English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Korean, Swedish, Russian, Arabic, Indonesian, Portuguese
Menu Languages		English, French, German, Spanish, Italian, Norwegian, Dutch, Simplified Chinese, Traditional Chinese, Korean, Russian, Polish, Turkish, Arabic, Indonesian, Portuguese, Vietnamese, Czech, Romanian, Hungarian, Malay, Hindi, Filipino, Farsi, Japanese, Thai
Operating Pitch/Roll		360 degree operation
Illumination Technology		LED, InFocus Quantum Color Engine
Display Technology		DLP .47" S410
Uniformity		JBMA 85% ANSI 70%
Zoom Ratio		Fixed
Throw and Zoom		
Throw Distance – Minimum		0.8 m
Throw Distance – Maximum		8.0 m
Throw Ratio		1.20:1
Shipping		
Product Dimensions		2.2 x 11.7 x 7.9 in / 55.9 x 297.2 x 199.9 mm
Product Weight		4.4 lbs / 2 kg

* Product specifications, terms, and offerings are subject to change at any time without notice.

Accessories

- Universal Projector Ceiling Mount (PRJ-MNT-UNIV)
- Replacement Remote for Select InFocus Projectors (INA-REMPJ001a)
- SimpleShare Presentation System (INA-SIMPS1)
- LiteShow 4 DB+ Dual Band Wireless Adapter (INLITESHOW4DB+)
- LiteShow Mount Adapter (PRJ-MNT-LS3)
- SimpleShare Touch Presentation System (INA-SIMINT1)
- SimpleShare (INA-SIMS1)
- DLP Link 3D Glasses by XPAND (X103-EDUX3-R1)

Soft Projector Carry Case (CA-SOFTCASE-VAL3)

Manual Pull Down Projector Screen: 92 in., 16:9 (SC-PDHD-92)

Manual Pull Down Projector Screen: 106 in., 16:9 (SC-PDHD-106)

Manual Pull Up Projector Screen: 73 in., 16:9 (SC-PUW-73)

Manual Pull Up Projector Screen: 90 in., 16:9 (SC-PUW-90)

1 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM1)

2 Year Extended Warranty for IN1XXX, IN2XXX, IN3XXX Projectors (EPW-PJM2)